

STORM/HDSPARK Comparison Guide

			∞ 6000 = 60 1	₽0000 = 0000		
		HADRING SOUTH OF THE PARTY OF T		. 5000 500 8	2 0 12 0 10 15 15 15 15 15 15 15 15 15 15 15 15 15	
	STORM 3G Elite	STORM 3G	STORM Mobile (BOB)	STORM Mobile (Bay)	HDSPARK Pro	HDSPARK
Form factor	Breakout box	PCIe board	Breakout box	Bay + PCle board	PCIe board	PCIe board
Host connection	PCI Express x4 or ExpressCard/34	PCI Express x4	PCI Express x1 or ExpressCard/34	PCI Express x1	PCI Express x1	PCI Express x1
Host PC	Desktop/laptop	Desktop	Desktop /laptop	Desktop	Desktop	Desktop
Hardware encoder	Yes (HQ)	_	_	_	_	_
3G SDI support	Yes	Yes	_	_	_	_
10-bit I/O	Yes	Yes	_	_	_	_
1080p50/60 support	Yes (PCI Express x4 only)	Yes	_	_	_	_
Hardware real-time downconversion	Yes	_	Yes	Yes	_	_
Full duplex architecture	Yes	Yes	_	_		_
Video In						
HD/SD-SDI	2 (3G)	1 (3G)	_	_	_	_
HDMI	1	_	1	1	_	_
HD/SD component	1	_	1	1	_	_
S-Video	_	_	1 (common connector with component)	1 (common connector with component)	_	_
Composite	1	_	1	1	_	_
Video Out						
HD/SD-SDI	2 (3G)	1 (3G)	_	-	1	_
HDMI	1	1	1	1	_	1
HD/SD component	1	_	1	1	_	_
S-Video	_	_	1 (common connector with component)	1 (common connector with component)	_	_
Composite	1	_	1	1	_	_

	STORM 3G Elite	STORM 3G	STORM Mobile (BOB)	STORM Mobile (Bay)	HDSPARK Pro	HDSPARK
Audio In						
SDI embedded audio	8-channel	8-channel	_	_	_	_
AES/EBU audio	8-channel	_	_	_	_	_
HDMI embedded audio	8-channel	_	8-channel	8-channel	_	
Balanced audio	4-channel	_	_	_	_	_
Unbalanced audio (RCA pin)	_	_	2-channel	2-channel	_	_
Voiceover in	1 (phantom power available)	_	_	_	_	_
Audio Out						
SDI embedded audio	8-channel	8-channel	_	_	8-channel	_
AES/EBU audio	8-channel	_	_	_	2-channel	_
HDMI embedded audio	8-channel	8-channel	8-channel	8-channel	_	8-channel
Balanced audio	4-channel	_	_	_	_	_
Unbalanced audio (RCA pin)	_	_	2-channel	2-channel	2-channel	2-channel
Monitor audio out	2-channel balanced/ 2-channel unbalanced	_	_	_	_	_
Headphone	1	_	1 (stereo mini jack)	1 (stereo mini jack)	_	_
Others						
REF	1 in/1 out	1 in 2 out (with option)*	_	_	_	_
LTC	1 in/1 out	1 in (Option)	_	_	_	_
RS-422	2	1	_	_	_	_

^{*} Main board has 1 REF input but no output. Optional daughter card has 1 LTC in and 2 REF outs.

SALES

Local and regional sales contacts can be found by visiting www.grassvalley.com/sales

SUPPORT

Local and regional support contacts can be found by visiting www.grassvalley.com/support Join the Conversation at **GrassValleyLive** on Facebook, Twitter, and YouTube.







